

WHAT IS CLAIMED IS:

1. A dry measuring test device, comprising a reagent layer comprising a reagent containing a chromogen and a matrix which retains said reagent in the form of a layer, for determining a substance to be measured in a liquid sample by measuring the degree of coloring of the chromogen generated through the reaction between the substance to be measured and the reagent in terms of reflectance of light entered into the reagent layer, wherein said reagent layer comprises polymer beads embedding light reflective particles.

2. The dry measuring test device as claimed in Claim ⁶1, wherein said light reflective particles are selected from the group consisting of titanium dioxide, zinc oxide, barium sulfate, magnesium oxide, iron (III) oxide and iron (III) hydroxide.

3. The dry measuring test device as claimed in Claim ⁶1, wherein said polymer beads contain as a main component a high molecular compound selected from the group consisting of: polymer or copolymer having as a main component monomers selected from the group consisting of acrylic acid, methacrylic acid, maleic acid, ester of these substances, styrene, and alkylstyrene; polyurethane; polyurea; polyethylene; polypropylene; and polyvinyl chloride.

4. The dry measuring test device as claimed in Claim ⁶1, wherein an average particle diameter of the

polymer beads ranges from 1 to 40 μm .

5. The dry measuring test device as claimed in Claim 4, wherein the light reflective particles are contained in an amount of 10 to 70 w/v% based on the total content of the polymer beads, and the polymer beads are contained in an amount of 5 to 80 wt% based on the total weight of the reagent layer.

6. A dry measuring test device, comprising a reagent layer comprising a reagent containing a chromogen and a matrix which retains said reagent in the form of a layer, for determining a substance to be measured in a liquid sample by measuring the degree of coloring of the chromogen generated through the reaction between the substance to be measured and the reagent in terms of reflectance of light entered into the reagent layer, wherein a light blocking layer containing light blocking particles is laminated on the reagent layer.

7. The dry measuring test device as claimed in Claim 6, wherein the light blocking particles are selected from the group consisting of carbon black, iron (II) oxide, iron (II)iron (III) oxide, phthalocyanine blue, and phthalocyanine green.

8. The dry measuring test device as claimed in Claim 6, wherein the light blocking particles are contained in an amount of 15 to 90 wt% based on the total weight of the light blocking layer.

9. The dry measuring test device as claimed in

00959123 102297 262201 33755680

Claim 6, wherein the light blocking particles are contained in the light blocking layer in the form of polymer beads embedding them.

10. The dry measuring test device as claimed in
5 Claim 9, wherein the polymer beads contain as main component a high molecular compound selected from the group consisting of: polymer or copolymer having as the main component monomers selected from the group
10 consisting of acrylic acid, methacrylic acid, maleic acid, ester of these substances, styrene, and alkylstyrene; polyurethane; polyurea; polyethylene; polypropylene; and polyvinyl chloride.

11. The dry measuring test device as claimed in
15 Claim 9, wherein the light blocking particles are contained in an amount of 10 to 70 w/v% based on the total content of the polymer beads, and the polymer beads are contained in the light blocking layer in an amount of 30 to 90 wt% based on the total weight of the light blocking layer.

20 12. The dry measuring test device as claimed in Claim 9, wherein an average particle diameter of the polymer beads ranges from 1 to 40 μm .

13. The dry measuring test device as claimed in
25 Claim 6, wherein the reagent layer further contains the polymer beads embedding the light reflective particles.

Add
C27
Add
C27